

Technical Data Specification Sheet

Flash PE packed 10g Molecular Sieve Desiccant

Product Flash PE packed 10g Molecular Sieve Desiccant

Product Code 2MSTG007A

Raw Material 0.5~1.0mm 4A molecular sieve

Packaging Material Flash PE

Technical Standard

Items	Standard
Appearance	The surface of desiccant bag should not have damage or obvious discoloration, with the flat paper. The printing is clear without stains.
Loss on Drying (575 ± 25°C)	≤4.5%
Moisture adsorption capacity 25°C	RH=40% ≥15.0%
	RH=80% ≥16.5%
Dropping resistance	In the case of free falling of 15 times at a height of 1.2m or more, the desiccant bag shall not be broken or have the damage of enabling the adsorbent to leak.
Decoloring test	The soaked solution should be colorless.
Total residual solvents	≤5mg/m ²
Benzene residues	Not detectable
* Lead	≤5ppm
Paper bag fluorescence	No flaky fluorescence
Total bacterial count (cfu / bag)	≤10 ³
Mould and yeast count (cfu / bag)	≤10 ²
Escherichia coli	Not detectable per bag

Sachet Dimension
 Net Weight: 9.5~11.0g
 Width: 38±1mm
 Length: 90±4mm

Sealing Method Back Seal

Printing Wisemini



Technical Data Specification Sheet

Flash PE packed 10g Molecular Sieve Desiccant

- STD Packaging** — 750pcs/PE bag/pail
Pail Size: $\phi 275 \times 345$ mm, 48 drums/pallet
— product label contains below:
Manufacturer
Product
Description
Quantity per carton
Batch No.
MADE IN USA

- Storage** Shelf life: 2 years
Desiccant must always be kept in airtight containers to avoid moisture.

- Notes** The data given here is based on current knowledge and experience. This document is designed to describe the products in terms of their safety requirements. The above details do not imply any guarantee concerning composition, properties or performance. User is liable for his own operation.

2023-02-14

